



TOPPER 12

FLUSH MOUNT CEILING

location:
DAMP

SPECIFICATIONS:

DESCRIPTION

Flush-mounted ceiling fixture, featuring fused 3-piece glass diffuser.

LAMPING

Halogen: 40W low-pressure G9 Halogen 120V lamps, included.

LED: 16W Integrated source, 120V, dimmable, 85+ CRI, 3000°K CCT, 1600 lumens, 30,000 hours, included.

DIFFUSER

Handcrafted glass diffuser in Opal Glossy with clear or smoke trim.
12" Dia. x 3" H

CONSTRUCTION

Stamped aluminum fitter is powder coated white.

MOUNTING


Installs directly to a 4" octagonal outlet box, centered on fixture.
90°C supply wire required for incandescent lamping.

LABELS

UL or ETL Listed. Suitable for Damp Locations (interior use only).



OPAL/SMOKE (TOPPERSMC)



TOPPER12CLC
OPAL/CLEAR



ORDERING:

FIXTURE/DECOR	LAMP OPTIONS
TOPPER12CLC 12" Dia. Opal/Clear	HAL 2x40W G9 Hal
TOPPER12SMC 12" Dia. Opal/Smoke	LED 16W LED 120V, 1500 lumens

Ex. TOPPER12CLC-LED
Topper 12 Ceiling, Opal/Clear Stone Shade

Project Information:

All dimensions provided are nominal.
Allowance must be made for dimensional tolerance in handcrafted glasses.